

PLAM OPACIZZANTE

for sealers

DESCRIPTION

Plam Opacizzante Isoplam[®] is a special concentrated liquid additive with high opacifying and slight thickening power, specially designed to achieve an evenly opaque effect. Added to Plam Sealing solvent-based acrylic resins and polyurethane resins Plam Pol and Plam Pol Water Isoplam[®], it gives them an excellent opaque aesthetic performance.

FIELDS OF USE

It is used, diluted in sealers, on all surfaces in which an opaque finish is required.

TECHNICAL CHARACTERISTICS

Appearance	White fluid
Composition and phase	Aqueous solution of opacifying agents
Solid content	Ca 12%
Flammable point	30°C
Specific weight	0,985 kg/Lt

USAGE

Thoroughly mix Plam Opacizzante immediately before use by means of a mixing drill or mixer. The percentages of use vary according to the degree of opacity desired. A dosage percentage of 5% is recommended. In any case, do not exceed the dosage of 10% of product calculated on the amount of resin.

Pour Plam Opacizzante into the resin, mix thoroughly and apply the resin as usual. Take care to mix the mixture frequently during application.

The first coat of mixture applied may be slightly whitish. With the application of the second coat the whitish effect disappears. In any case, it is advisable to carry out preliminary tests on the dark supports to determine the most suitable percentage of Plam Opacizzante to be inserted into the resin. Plam Opacizzante, used in polyurethane resins, could highlight the sign of rolling: therefore, foresee the use of Deco Epox W BI before applying the sealer.

Important note:

The product has been tested on the Isoplam resins indicated above. It is recommended to always check compatibility with other types of resins.



CONSUMPTION

The amount of Plam Opacizzante to be used is at most about 10% by weight of the resin. Do not exceed the recommended doses.

CONTAINERS AND STORAGE

Plam Opacizzante Isoplam® is supplied in pots of Lt. 5.

The product is stored for 12 months at temperatures between 5 and 35°C. The production date is shown in the batch number, the batch numbers have the following meaning: year / month progressive production number.

It is afraid of frost and too high temperatures.

Once mixed with the resin, the mixture should be used within two months.

SAFETY

Consult the safety data sheet before use. Plam Opacifying Isoplam® is intended for professional use only.

IMPORTANTE:

Tutte le informazioni contenute in questa scheda sono basate sulle migliori esperienze pratiche e di laboratorio. E' responsabilità del cliente verificare che il prodotto sia adatto all'impiego cui si intende destinare. Il produttore declina ogni responsabilità per i risultati di applicazioni errate. Si consiglia di effettuare sempre delle prove su piccole superfici prima della applicazione. La presente scheda sostituisce e annulla le precedenti. I dati possono essere variati in ogni momento. Si ricorda inoltre che i prodotti Isoplam sono destinati all'uso professionale e che Isoplam provvede all'addestramento periodico dei propri clienti che ne fanno richiesta. Chiunque utilizzi questi prodotti senza esserne abilitato lo fa a proprio rischio.

ISOPLAM S.R.L.

Via E. Mattei, 4 – Z. I. Maser (TV) – Italia Tel. (+39) 0423 925023 www.isoplam.it
Azienda certificata UNI EN ISO 9001:2015

Rev. del 19.10.2022